

## WEST

Generate Collection

Print

L8: Entry 10 of 11

File: DWPI

Feb 16, 1980

DERWENT-ACC-NO: 1980-22814C

DERWENT-WEEK: 198013

COPYRIGHT 2003 DERWENT INFORMATION LTD

TITLE: Cathode for non-aq. electrolyte lithium-copper oxide battery - prepd. by compacting and sintering mixt. of pyrolysed copper salt, copper oxide and carbon

PATENT-ASSIGNEE:

ASSIGNEE
SANYO ELECTRIC CO

CODE

SAOL

PRIORITY-DATA: 1978JP-0095305 (August 1, 1978)

PATENT-FAMILY:

PUB-NO

PUB-DATE

LANGUAGE

PAGES MA

MAIN-IPC

JP 55021879 A 🗸

February 16, 1980

000

JP 86055739 B

November 28, 1986

000

INT-CL (IPC): H01M 4/08

ABSTRACTED-PUB-NO: JP 55021879A

BASIC-ABSTRACT:

Copper salt, e.g. copper nitrate, hydroxide or carbonate and copper oxide are mixed and heated to pyrolyse the salt into copper oxide. <u>Carbon</u> is added to the mixt. which is then compacted and sintered to form a <u>cathode</u>. The <u>cathode</u> is used in a lithium-copper oxide battery. The copper oxide serves as active material.

In an example, copper hydroxide powder and copper oxide powder are mixed and heated at 800 degrees C in an inert gas atmos. for 10-20 mins. to thermally decompose the copper hydroxide into copper oxide. 90 wt.% of the mixt. contg. the thermally decomposed products, 6 wt.% of acetylene black and 4 wt.% of PTFE powder are mixed and compacted into a plate. The plate is heated at 300 degrees C to make a cathode contg. high-activity copper oxide.

TITLE-TERMS: <u>CATHODE</u> NON AQUEOUS ELECTROLYTIC LITHIUM COPPER OXIDE BATTERY PREPARATION COMPACT SINTER MIXTURE PYROLYSE COPPER SALT COPPER OXIDE CARBON

DERWENT-CLASS: A85 L03 X16

CPI-CODES: A12-E06; L03-E01B;

POLYMER-MULTIPUNCH-CODES-AND-KEY-SERIALS:

Key Serials: 0210 0231 0947 1995 1996 2198 2200 2201 2541 2682 2739

Multipunch Codes: 011 04- 062 064 087 23& 231 236 359 393 60- 609 623 627 688 726